



IP68 快速防水接线器/Quick waterproof connector

M684-Y






产品参数/Technical data


型号 Model	M684-Y	
材料 Material	防火阻燃 Fire and flame retardant UL94V-2	
额定输出 Rated output	IEC/NSW:24A 450VAC ETL:10A 300VAC	
防护等级 IP code	IP68	
接线内芯 Terminal	2P/3P	
工作温度 Working	T105	
接线范围 Rated connecting capacity	欧规 European:0.5 ~ 2.5mm² 澳规 Australia:0.5 ~ 2.5mm² 美规 American: SJOW 14-18AWG	
密封胶塞/seal plug		
胶塞孔径/plug aperture	8mm	11mm
适用线径/Available cable diameter (橡胶圆线/Round rubber cable)	3*M20(4-8mm)	3*M20(6-11mm)
防水测试 Testing	20M 150hours	
参考剥线长度 Refer to stripping length	10mm (0.5~1.0mm²) rigid 15mm (1.5~2.5mm²) rigid	
产品尺寸 Product Size(参考实际尺寸图)	128.3*65.9*25.4mm (Refer to actual drawing)	
认证 Certification	ENEC,CE,UKCA,ETL,NSW,CB,ROHS	
产品质保/Product warranty	1 年/ one year	
产品应用/Application	水底/Underwater(淡水 fresh water) 地埋/Underground	
注/Mark: 1.不能使用在盐碱土壤/Do not use in saline soil 2.不能长期接触油性物质或浸泡在油污中/Do not contact oily substances or soak in oil for a long time 3.不建议长期在日照暴晒下使用/Long time exposed under sunshine is not recommended		



产品图纸/Product drawings



参考剥线长度
Refer to stripping length



接线步骤/Wiring steps

01

扭开两端螺帽套筒
取出接线内芯

Open the nut cover at
both end
sides,take out quick
connector



02

将电缆穿过螺帽主体
扳起卡扣

Thread the cable
through the
nut body and pull up
the buckle



03

两端电缆线相对应插入
自锁接线内芯, 将卡扣
压合锁住线材即可

Connect the wires to the
3 core
pressed terminal corre-
spondantly
press the levers



04

拧紧两端螺帽主体
接线完成

Twist and tighten the
cable glands

