



深圳格林威电子
GREENWAYCS

Tel: +0755-29756655

Fax: +0755-29756646

IP68 防水接线器/ waterproof connector

M683-B(2P/3P)



NSW

UK
CA

CB

RoHS

ADD: Building 90, 2nd Industrial area, Lisonglang Community, Gongming Street, Guangming District, Shenzhen, China

中国·广东省·深圳市·光明区公明街道李松荫社区第二工业区 90 栋

Website: www.greenwaycs.com




产品参数/Technical data

型号 Model	M683-B
材料 Material	防火阻燃 Fire and flame retardant UL94V-2
额定输出 Rated output	IEC/NSW:17.5A 450VAC ETL:10A 300VAC
防护等级 IP code	IP68
接线内芯 Terminal	2P/3P
工作温度 Working	T105
接线范围 Rated connecting capacity	欧规 European:0.5 ~ 1.5mm ² 澳规 Australia:0.5 ~ 1.5mm ²
密封胶塞/seal plug	
胶塞孔径/plug aperture	10mm
适用线径/Available cable diameter (橡胶圆线/Round rubber cable)	2*M18(5-10mm)
防水测试 Testing	20M 150hours
参考剥线长度 Refer to stripping length	外剥线 External stripping 20mm 内剥线 Internal stripping 8mm
产品尺寸 Product Size(参考实际尺寸图)	93.4*24.3mm (Refer to actual drawing)
认证 Certification	ENEC,CE,UKCA,ETL,NSW,CB,ROHS
产品质保/Product warranty	1 年/ one year
产品应用/Application	水底/Underwater(淡水 fresh water) 地埋/Underground
注/Mark: 1.不能使用在盐碱土壤/Do not use in saline soil 2.不能长期接触油性物质或浸泡在油污中/Do not contact oily substances or soak in oil for a long time 3.不建议长期在日照暴晒下使用/Long time exposed under sunshine is not recommended	




产品图纸/Product drawings



参考剥线长度

Refer to stripping length





接线步骤/Wiring steps

01

扭开两端螺帽套筒，取出接线内芯

Open the nut cover at both end sides, take out quick connector



02

将线材穿过螺帽套筒

Thread the cable through the nut



03

线材插入接线内芯后螺丝固定

The wire is inserted into the inner core of the connection and fixed by a screw



04

拧紧两端螺帽主体，接线完成

Twist and tighten the cable glands

